

# Coating Development Group, Inc.

## **Floor Coatings**

Restore your dirty old floors with **CDG Floor Coatings** for plastic, ceramic and many other surfaces.

Apply a new color coat and give life to those surfaces without the need for major stripping, cleaning or replacement.

**CDG Floor Coatings** are durable, environmentally friendly and easy to apply.



**Just sweep and mop surface**

**Roll, brush or spray on coatings**

**Self-crosslinking waterborne materials**

**Low VOC's and HAP's content**

**Coverage from 250 to 300 sq. ft./gallon**

**Easy cleanup**

**2 or 3-step systems available:**

**Sealer** (optional for maximum adhesion)

**Colored basecoats** (black, white, grey and beige) 5-gallon minimum order. Custom colors available at a 50% premium and a 50-gallon minimum order.

**Clear topcoat** (CDG's or comparable brand)

**Coating Development Group, Inc.**  
**[www.cdgclearkin.com](http://www.cdgclearkin.com)**  
**215-426-6216**





## Coating Development Group, Inc

### Floor Coatings

#### *Floor Preparation and Coatings Applications*

Clean of floor tiles, prior to coating application.

- Sweep surface of old floor.
- Mop with soapy water
- Wet mop and dry surface.

Application recommendations

- Roller (short nap)
- Brush
- Spray
- Sponge mop

Drying schedules

- Sealer coat
  - Apply one coat and air dry 16 hours before applying color coats.
- Color coats
  - Apply one - two coats, depending on application and color, with 4-6 hours drying between coats. Drying time is dependent on relative humidity conditions. Longer drying of 8-10 hours may be required above 60% R.H.
- Clear topcoats
  - Apply over color coats and follow directions of manufacturer of clear topcoat. CDG clear topcoats require 16 hours air dry before walking on coated surface.

Equipment Clean-up

- All coatings can be removed from application equipment by washing with soapy water and rinsing with clear water.