

MATERIAL SAFETY DATA SHEET

MSDS Name: WIPING STAIN BASE  
 MSDS Number: #WM-195  
 Version Number  
 MSDS Date: AUG-13-2007  
 Page Number: 1 of 8

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: WIPING STAIN BASE  
 CAS Number: MIXTURE  
 Hazard Rating: Health: 2 Fire: 3 Reactivity: 0 PPI: H

Company Identification: COATING DEVELOPMENT GROUP, INC  
 P.O. BOX 14817  
 SCHILLER & ALLEN STREETS  
 PHILADELPHIA PA 19134-4817

Contact: MARK KOCHANOWICZ  
 Telephone/Fax: (215) 426-6216 (215) 426-6219  
 Emergency Phone (24 Hour): CHEMTREC  
 (800) 424-9300

Product Class: STAINS  
 Trade Name: WIPING STAIN BASE  
 Product Code: #WM-195

SECTION II - INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
MINERAL SPIRITS HMIS Health: 1 Fire:2 Reactivity:0 PPI:H_____	8052-41-3	43.42	
HI FLASH NAPHTHA HMIS Health: 1 Fire:2 Reactivity:0 PPI:H_____	64742-95-6	18.11	
PSEUDOCUMENE HMIS Health: 2 Fire:2 Reactivity:0 PPI:H_____	95-63-6	10.56	
PNB HMIS Health: 1 Fire:2 Reactivity:0 PPI:H_____	5131-66-8	6.36	
WATER HMIS Health: 0 Fire:0 Reactivity:0 PPI: _____	7732-18-5	4.66	
TOLUENE	108-88-3	2.64	

MATERIAL SAFETY DATA SHEET

MSDS Name: WIPING STAIN BASE  
MSDS Number: #WM-195  
Version Number  
MSDS Date: AUG-13-2007  
Page Number: 2 of 8

---

HMIS Health: 2 Fire:3 Reactivity:0 PPI:H\_\_\_\_\_

XYLENE 1330-20-7 1.17

HMIS Health: 2 Fire:3 Reactivity:0 PPI:H\_\_\_\_\_

PROPYLENE GLYCOL METHYL ETHER 107-98-2 0.60

HMIS Health: 1 Fire:3 Reactivity:0 PPI:B\_\_\_\_\_

CUMENE 98-82-8 0.42

HMIS Health: 2 Fire:3 Reactivity:0 PPI:H\_\_\_\_\_

MESITYLENE 108-67-8 0.18

HMIS Health: 2 Fire:2 Reactivity:0 PPI:H\_\_\_\_\_

METHANOL 67-56-1 0.12

HMIS Health: 3 Fire:3 Reactivity:0 PPI:H\_\_\_\_\_

\*\*\* ALL Ingredients in this product are listed in the T.S.C.A. Inventory

SECTION III - HAZARDS IDENTIFICATION

EYE CONTACT - Exposure may cause eye irritation. Symptoms may include stinging, tearing and redness.

INGESTION - Harmful or fatal if swallowed. Pulmonary aspiration hazard if swallowed and/or vomiting occurs - can enter lungs and cause damage.

INHALATION - Excessive exposures may cause irritation to eyes, nose, throat, lungs; respiratory tract; central nervous system (brain) effects; headaches, nausea; dizziness, loss of balance and coordination; unconsciousness, coma; respiratory failure and death. Repeated excessive exposures may cause liver effects or damage; kidney effects or damage.

SKIN - Skin absorption of material may produce systemic toxicity. May cause irritation with prolonged or repeated contact. Removes natural oil and fats from skin.

SECTION IV - FIRST AID MEASURES

EYE CONTACT - Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment.

---

MATERIAL SAFETY DATA SHEET

MSDS Name: WIPING STAIN BASE  
MSDS Number: #WM-195  
Version Number  
MSDS Date: AUG-13-2007  
Page Number: 3 of 8

-----

INGESTION - DO NOT INDUCE VOMITING! This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with head down. Seek medical attention. If possible, do not leave individual unattended.

INHALATION - Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician.

SKIN CONTACT - Wash affected areas with soap and water. Remove contaminated clothing and shoes. Obtain medical attention if irritation persists. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

SECTION V - FIRE-FIGHTING MEASURES

Flammability Class	IC
Flash Range:	94.0F (34.44oC) Setaflash
Explosive Range:	Not Available

Use foam, carbon dioxide (CO2) or dry chemical. Water may not be effective to extinguish fire. Use water spray to cool fire-exposed containers and to protect personnel.

Keep personnel removed from and upwind of fire. Wear full fire-fighting turn-out gear (full bunker gear), and respiratory protection (SCBA). Cool container with water spray.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Contain spilled liquid with sand or earth. DO NOT use combustible materials, such as sawdust.

Eliminate all ignition sources, use explosion-proof equipment. The very fine particles can cause fire or explosion. Vacuum or sweep material and place in a disposal container. Obey all local, state and federal laws regarding chemical spills.

SECTION VII - HANDLING AND STORAGE

-----

MATERIAL SAFETY DATA SHEET

MSDS Name: WIPING STAIN BASE  
 MSDS Number: #WM-195  
 Version Number  
 MSDS Date: AUG-13-2007  
 Page Number: 4 of 8

PRECAUTIONS TO BE TAKEN - Closed containers may explode when exposed to extreme heat. Store away from high temperatures, sparks and flames. Avoid prolonged skin contact. Do not breath spray mist. Ground containers while pouring and limit free fall to a few inches to prevent static sparks. Avoid spontaneous combustion of contaminated rags and other easily ignitable organic accumalations (such as spray booth residues) by immediate immersion in water. Emptied containers may retain hazardous properties. Do not cut, puncture or weld on or near the container. Store large quantities only in buildings designed to comply with OSHA 1910.106.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
MINERAL SPIRITS	100.00 PPM	N/est	N/est	N/est	100.00 PPM
HI FLASH NAPHTHA	25.00 PPM	N/est	N/est	N/est	25.00 PPM
PSEUDOCUMENE	25.00 PPM	N/est	N/est	N/est	N/est
PNB	N/est	N/est	N/est	N/est	N/est
WATER	N/est	N/est	N/est	N/est	N/est
TOLUENE	50.00 PPM	N/est	N/est	N/est	100.00 PPM
XYLENE	100.00 PPM	N/est	N/est	N/est	100.00 PPM
PROPYLENE GLYCOL METHYL ETHER	100.00 PPM	N/est	N/est	N/est	100.00 PPM
CUMENE	50.00 PPM	N/est	N/est	N/est	50.00 PPM

MATERIAL SAFETY DATA SHEET

MSDS Name: WIPING STAIN BASE  
 MSDS Number: #WM-195  
 Version Number  
 MSDS Date: AUG-13-2007  
 Page Number: 5 of 8

MESITYLENE	N/est	N/est	N/est	N/est	N/est
METHANOL	200.00 PPM	N/est	N/est	N/est	200.00 PPM

RESPIRATORY PROTECTION - Provide adequate ventilation. If TLV of the product is exceeded, a NIOSH/MSHA jointly approved self-contained breathing apparatus with a full facepiece operated in pressure demand or other positive pressure mode is advised.

VENTILATION - Provide sufficient mechanical and/or local exhaust ventilation to maintain exposure below TLV.

PROTECTIVE GLOVES - Wear resistant gloves such as Buna-N (nitrile rubber).

EYE PROTECTION - Chemical splash goggles in compliance with OSHA regulations are advised.

OTHER PROTECTIVE EQUIPMENT - To prevent prolonged skin contact, wear impervious clothing and boots. Maintain an eyewash facility and an emergency shower.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form:	LIQUID
Appearance/Color:	TRANSLUSCENT
Odor:	PETROLEUM DISTILLATE
Solubility (in water):	INSOLUBLE
pH Value:	Not Available
Boiling Range:	147.oF - 398.oF (63.89oC - 203.33oC)
Vapor Pressure (mmHg):	Not Available
Melting Point:	Not Available
Evaporation Rate:	0.08 times Slower than n-Butyl Acetate
Vapor Density:	Heavier than air
Partition Coefficient	Not Available
% Volatile Weight	88.02%
% Volatile	BY VOLUME 91.65%
Specific Gravity:	0.86536

MATERIAL SAFETY DATA SHEET

MSDS Name: WIPING STAIN BASE  
MSDS Number: #WM-195  
Version Number  
MSDS Date: AUG-13-2007  
Page Number: 6 of 8

---

VOC 6.96 VOC/NV LBS  
Molecular Weight: N/A  
Heavy Elements (ppm) 0.

SECTION X - STABILITY AND REACTIVITY

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur

SECTION XI - TOXICOLOGICAL INFORMATION

Route	Species	Exposure and Dose
PSEUDOCUMENE		
Inhalation	Rat, adult	LC50 18. PPM
Oral	Rat, adult	LD50 5. PPM
TOLUENE		
Oral	Rat, adult	LD50 5000. PPM
CUMENE		
Inhalation	Rat, adult	LC50 8000. PPM
Oral	Rat, adult	LD50 1400. PPM
METHANOL		
Inhalation	Rat, adult	LC50 64000. PPM
Oral	Rat, adult	LD50 5628. PPM

SECTION XII - ECOLOGICAL INFORMATION

No data available.

SECTION XIII - DISPOSAL CONSIDERATIONS

Empty containers should be washed and discarded.

Empty containers should not be used for other purposes. Disposal should be in accordance with local, state or national legislation.

---

MATERIAL SAFETY DATA SHEET

MSDS Name: WIPING STAIN BASE  
 MSDS Number: #WM-195  
 Version Number  
 MSDS Date: AUG-13-2007  
 Page Number: 7 of 8

SECTION XIV - TRANSPORT INFORMATION

UN Number UN1263  
 UN Pack Group III  
 UN Class 3  
 Emergency Storage N/A  
 MFAG Table Number N/A  
 Kemmler Code N/A  
 ICAO/IATA Class N/A  
 IMDG Class N/A  
 Shipping Name PAINT, 3, UN1263, III  
 DOT Hazard Class  
 Technical Name

SECTION XV - REGULATORY INFORMATION

SARA TITLE III SECTION 313:  
 This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
PSEUDOCUMENE	95-63-6	10.56
TOLUENE	108-88-3	2.64
XYLENE	1330-20-7	1.17
CUMENE	98-82-8	0.42
METHANOL	67-56-1	0.12

-PROP 65 (TERATOGEN)

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Percent
TOLUENE	108-88-3	2.64

SECTION XVI - OTHER INFORMATION

MATERIAL SAFETY DATA SHEET

MSDS Name: WIPING STAIN BASE

MSDS Number: #WM-195

Version Number

MSDS Date: AUG-13-2007

Page Number: 8 of 8

---

NOTICE - Reports have associated repeated and prolonged occupational exposures with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DISCLAIMER:

The information contained herein applies only to the material identified on this MSDS. The data presented in these sheets are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of this product and is accurate to the best of our knowledge at the date of issue of this MSDS. Coating Development Group, Inc. makes no warranty with respect to the accuracy of the information provided by its suppliers and disclaims all liability of reliance thereon. Coating Development Group, Inc. warrants only that its products conform to their published specifications. We do not guarantee favorable results and we assume no liability in connection with the use of this product. Final determination of the use of this product is the sole responsibility of the user. Although certain hazards are described herein, it cannot be guaranteed that these are the only hazards that exist. All chemicals may present unknown health hazards and should be used with caution. Read all labels.