

MATERIAL SAFETY DATA SHEET

MSDS Name: PEWTER GLAZE
 MSDS Number: WM-9006
 Version Number
 MSDS Date: JUN-21-2007
 Page Number: 1 of 9

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: PEWTER GLAZE
 CAS Number: MIXTURE
 Hazard Rating: Health: 2 Fire: 3 Reactivity: 0 PPI: H

Company Identification: COATING DEVELOPMENT GROUP, INC
 P.O. BOX 14817
 SCHILLER & ALLEN STREETS
 PHILADELPHIA PA 19134-4817

Contact: MARK KOCHANOWICZ
 Telephone/Fax: (215) 426-6216 (215) 426-6219
 Emergency Phone (24 Hour): CHEMTREC
 (800) 424-9300

Product Class: STAINS
 Trade Name
 Product Code: WM-9006

SECTION II - INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
NAPHTHA, HEAVY AROMATIC PETR HMIS Health: 2 Fire:2 Reactivity:0 PPI:H____	64742-94-5	18.48	
MINERAL SPIRITS HMIS Health: 1 Fire:2 Reactivity:0 PPI:H____	8052-41-3	16.94	
IRON OXIDES HMIS Health: 2 Fire:1 Reactivity:1 PPI:H____	1309-37-1	4.54	
NAPHTHA, HEAVY ALKYLATED PET HMIS Health: 2 Fire:2 Reactivity:0 PPI:H____	64741-65-7	2.75	
HYDROTREATED KEROSENE HMIS Health: 1 Fire:2 Reactivity:0 PPI:H____	64742-47-8	2.23	
NAPHTHALENE	91-20-3	2.07	

MATERIAL SAFETY DATA SHEET

MSDS Name: PEWTER GLAZE
 MSDS Number: WM-9006
 Version Number
 MSDS Date: JUN-21-2007
 Page Number: 2 of 9

HMIS Health: 2	Fire:2	Reactivity:0	PPI:H____	
KEROSENE			8008-20-6	1.75
HMIS Health: 1	Fire:2	Reactivity:0	PPI:H____	
PSEUDOCUMENE			95-63-6	1.40
HMIS Health: 2	Fire:2	Reactivity:0	PPI:H____	
HI FLASH NAPHTHA			64742-95-6	1.11
HMIS Health: 1	Fire:2	Reactivity:0	PPI:H____	
VM&P NAPHTHA			64742-89-8	0.90
HMIS Health: 1	Fire:3	Reactivity:0	PPI:H____	
WATER			7732-18-5	0.69
HMIS Health: 0	Fire:0	Reactivity:0	PPI: ____	
CARBON BLACK			1333-86-4	0.48
HMIS Health: 1	Fire:1	Reactivity:0	PPI:C____	
ETHYL ALCOHOL ANHYDROUS			64-17-5	0.21
HMIS Health: 1	Fire:3	Reactivity:0	PPI:H____	
XYLENE			1330-20-7	0.13
HMIS Health: 2	Fire:3	Reactivity:0	PPI:H____	
FORMALDEHYDE			50-00-0	0.08
HMIS Health: 2	Fire:2	Reactivity:1	PPI:X____	

*** ALL Ingredients in this product are listed in the T.S.C.A. Inventory

SECTION III - HAZARDS IDENTIFICATION

EYE CONTACT - Exposure may cause eye irritation. Symptoms may include stinging, tearing and redness.

INGESTION - Harmful or fatal if swallowed. Pulmonary aspiration hazard if swallowed and/or vomiting occurs - can enter lungs and cause damage.

INHALATION - Excessive exposures may cause irritation to eyes, nose, throat, lungs; respiratory tract; central nervous system (brain) effects; headaches, nausea; dizziness, loss of balance and coordination; unconsciousness, coma; respiratory failure and death.

MATERIAL SAFETY DATA SHEET

MSDS Name: PEWTER GLAZE
MSDS Number: WM-9006
Version Number
MSDS Date: JUN-21-2007
Page Number: 3 of 9

Repeated excessive exposures may cause liver effects or damage; kidney effects or damage.

SKIN - Skin absorption of material may produce systemic toxicity. May cause irritation with prolonged or repeated contact. Removes natural oil and fats from skin.

CANCER HAZARDS

CONTAINS FORMALDEHYDE - Inhalation of formaldehyde vapor caused cancer in laboratory animal tests. Refer to Section XI for toxicology information on the OSHA regulated components of this product.

SECTION IV - FIRST AID MEASURES

EYE CONTACT - Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment.

INGESTION - DO NOT INDUCE VOMITING! This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with head down. Seek medical attention. If possible, do not leave individual unattended.

INHALATION - Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician.

SKIN CONTACT - Wash affected areas with soap and water. Remove contaminated clothing and shoes. Obtain medical attention if irritation persists. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

SECTION V - FIRE-FIGHTING MEASURES

Flammability Class	II
Flash Range:	50.oF - 230.oF (10.oC - 110.oC)
Explosive Range:	Not Available

Use foam, carbon dioxide (CO2) or dry chemical. Water may not be effective to extinguish fire. Use water spray to cool fire-exposed containers and to protect personnel.

Keep personnel removed from and upwind of fire. Wear full

MATERIAL SAFETY DATA SHEET

MSDS Name: PEWTER GLAZE
MSDS Number: WM-9006
Version Number
MSDS Date: JUN-21-2007
Page Number: 4 of 9

fire-fighting turn-out gear (full bunker gear), and respiratory protection (SCBA). Cool container with water spray.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Contain spilled liquid with sand or earth. DO NOT use combustible materials, such as sawdust.

Eliminate all ignition sources, use explosion-proof equipment. The very fine particles can cause fire or explosion. Vacuum or sweep material and place in a disposal container. Obey all local, state and federal laws regarding chemical spills.

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN - Closed containers may explode when exposed to extreme heat. Store away from high temperatures, sparks and flames. Avoid prolonged skin contact. Do not breath spray mist. Ground containers while pouring and limit free fall to a few inches to prevent static sparks. Avoid spontaneous combustion of contaminated rags and other easily ignitable organic accumalations (such as spray booth residues) by immediate immersion in water. Emptied containers may retain hazardous properties. Do not cut, puncture or weld on or near the container. Store large quantities only in buildings designed to comply with OSHA 1910.106.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
NAPHTHA, HEAVY AROMATIC PETR	N/est	N/est	N/est	N/est	100.00 PPM
MINERAL SPIRITS	100.00 PPM	N/est	N/est	N/est	100.00 PPM
IRON OXIDES	5.00 mg/M3	N/est	N/est	N/est	10.00 mg/M3

NAPHTHA, HEAVY ALKYLATED PET

MATERIAL SAFETY DATA SHEET

MSDS Name: PEWTER GLAZE
 MSDS Number: WM-9006
 Version Number
 MSDS Date: JUN-21-2007
 Page Number: 5 of 9

	300.00 PPM	N/est	N/est	N/est	N/est
HYDROTREATED KEROSENE	N/est	N/est	N/est	N/est	N/est
NAPHTHALENE	10.00 PPM	N/est	15.00 PPM	15.00 PPM	10.00 PPM
KEROSENE	N/est	N/est	N/est	N/est	N/est
PSEUDOCUMENE	25.00 PPM	N/est	N/est	N/est	N/est
HI FLASH NAPHTHA	25.00 PPM	N/est	N/est	N/est	25.00 PPM
VM&P NAPHTHA	300.00 PPM	N/est	N/est	N/est	100.00 PPM
WATER	N/est	N/est	N/est	N/est	N/est
CARBON BLACK	3.50 mg/M3	N/est	N/est	N/est	3.50 mg/M3
ETHYL ALCOHOL ANHYDROUS	1000.00 PPM	N/est	N/est	N/est	1000.00 PPM
XYLENE	100.00 PPM	N/est	N/est	N/est	100.00 PPM
FORMALDEHYDE	0.75 PPM	N/est	N/est	N/est	1.00 PPM

RESPIRATORY PROTECTION - Provide adequate ventilation. If TLV of the product is exceeded, a NIOSH/MSHA jointly approved self-contained breathing apparatus with a full facepiece operated in pressure demand or other positive pressure mode is advised.

VENTILATION - Provide sufficient mechanical and/or local exhaust ventilation to maintain exposure below TLV.

PROTECTIVE GLOVES - Wear resistant gloves such as Buna-N (nitrile)

MATERIAL SAFETY DATA SHEET

MSDS Name: PEWTER GLAZE
MSDS Number: WM-9006
Version Number
MSDS Date: JUN-21-2007
Page Number: 6 of 9

rubber).

EYE PROTECTION - Chemical splash goggles in compliance with OSHA regulations are advised.

OTHER PROTECTIVE EQUIPMENT - To prevent prolonged skin contact, wear impervious clothing and boots. Maintain an eyewash facility and an emergency shower.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form:	LIQUID
Appearance/Color:	BLACK
Odor:	PETROLEUM DISTILLATE
Solubility (in water):	INSOLUBLE
pH Value:	Not Available
Boiling Range:	171.oF - 617.oF (77.22oC - 325.oC)
Vapor Pressure (mmHg):	Not Available
Melting Point:	Not Available
Evaporation Rate:	0.025 times Slower than n-Butyl Acetate
Vapor Density:	Heavier than air
Partition Coefficient	Not Available
% Volatile Weight	48.98%
% Volatile	BY VOLUME 59.84%
Specific Gravity:	1.03713
VOC	0.95 VOC/NV LBS
Molecular Weight:	N/A
Heavy Elements (ppm)	0.

SECTION X - STABILITY AND REACTIVITY

Stability:	This product is stable
Hazardous Polymerization:	Hazardous polymerization will not occur

SECTION XI - TOXICOLOGICAL INFORMATION

Route	Species	Exposure and Dose
PSEUDOCUMENE		

MATERIAL SAFETY DATA SHEET

MSDS Name: PEWTER GLAZE
MSDS Number: WM-9006
Version Number
MSDS Date: JUN-21-2007
Page Number: 7 of 9

Inhalation	Rat, adult	LC50 18. PPM
Oral	Rat, adult	LD50 5. PPM

FORMALDEHYDE

Inhalation	Rat, adult	LC50 250. PPM
Oral	Rat, adult	LD50 800. PPM

Formaldehyde has oral (rat) and dermal (rabbit) LD50 values of 800 mg/kg and 270 mg/kg, respectively. The LC50 following a 4-hour inhalation exposure to rats is 250-478 ppm. Irritation of the nose and throat has been observed in people exposed to formaldehyde vapor levels in excess of 1 ppm. Normal breathing may be seriously impaired at levels above 10 ppm and serious lung damage can occur at levels exceeding 50 ppm. No pulmonary sensitization has been demonstrated in laboratory animal studies. Formaldehyde solutions can cause severe eye and moderate skin irritation. Repeated skin exposure to solutions of 2% or more formaldehyde has caused allergic skin reactions. Formaldehyde was found to be weakly mutagenic in a number of in vitro genotoxicity tests, but inactive in vivo. Formaldehyde did not cause birth defects in rats inhaling concentrations up to 10 ppm. Lifetime inhalation of formaldehyde vapor at concentrations above 5 ppm for 6 hours per day caused nasal tumors in laboratory animals. Epidemiology studies have failed to link cancer in humans with occupational exposure to formaldehyde. Formaldehyde is a chemical known to the State of California to cause cancer.

SECTION XII - ECOLOGICAL INFORMATION

No data available.

SECTION XIII - DISPOSAL CONSIDERATIONS

Empty containers should be washed and discarded.

Empty containers should not be used for other purposes. Disposal should be in accordance with local, state or national legislation.

SECTION XIV - TRANSPORT INFORMATION

UN Number	UN1263
UN Pack Group	III

MATERIAL SAFETY DATA SHEET

MSDS Name: PEWTER GLAZE
MSDS Number: WM-9006
Version Number
MSDS Date: JUN-21-2007
Page Number: 8 of 9

UN Class 3
Emergency Storage N/A
MFAG Table Number N/A
Kemmler Code N/A
ICAO/IATA Class N/A
IMDG Class N/A
Shipping Name PAINT, 3, UN1263, III
DOT Hazard Class
Technical Name

SECTION XV - REGULATORY INFORMATION

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
NAPHTHALENE	91-20-3	2.07
PSEUDOCUMENE	95-63-6	1.40
XYLENE	1330-20-7	0.13

SECTION XVI - OTHER INFORMATION

NOTICE - Reports have associated repeated and prolonged occupational exposures with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DISCLAIMER:

The information contained herein applies only to the material identified on this MSDS. The data presented in these sheets are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of this product and is accurate to the best of our knowledge at the date of issue of this MSDS. Coating Development Group, Inc. makes no warranty with respect to the accuracy of the information provided by its suppliers and disclaims all liability of reliance thereon. Coating Development Group, Inc.

MATERIAL SAFETY DATA SHEET

MSDS Name: PEWTER GLAZE

MSDS Number: WM-9006

Version Number

MSDS Date: JUN-21-2007

Page Number: 9 of 9

warrants only that its products conform to their published specifications. We do not guarantee favorable results and we assume no liability in connection with the use of this product. Final determination of the use of this product is the sole responsibility of the user. Although certain hazards are described herein, it cannot be guaranteed that these are the only hazards that exist. All chemicals may present unknown health hazards and should be used with caution. Read all labels.